




## HARCO PRICE LIST


### PHILMAC<sup>®</sup> UTC<sup>®</sup> COMPRESSION FITTINGS


Universal Transition Couplings


Repair Coupling (No Stop) Compression x Compression	SIZE	PART NUMBER	PIPE DIAMETER RANGE		CTN QTY	LIST PRICE
			inches	millimeters		
				B		
	C	75-608CC	1.06 - 1.34	27-34	25	\$36.86
	D	75-608DD	1.34 - 1.54	34-39	25	\$46.48
	E	75-608EE	1.54 - 1.69	39-43	20	\$42.19
	F	75-608FF	1.85 - 1.93	47-49	15	\$64.99
	G	75-608GG	2.32 - 2.40	59-61	10	\$80.66


Reducer Coupling Compression x Compression	SIZE	PART NUMBER	PIPE DIAMETER RANGE		CTN QTY	LIST PRICE
			inches	millimeters		
				BA		
	CB	75-617CB	1.06 - 1.34 x 0.83 - 1.06	27-34 x 21-27	35	\$36.33
	DC	75-617DC	1.34 - 1.54 x 1.06 - 1.34	34-39 x 27-34	25	\$68.18
	EC	75-617EC	1.54 - 1.69 x 1.06 - 1.34	39-43 x 27-34	20	\$42.11
	FE	75-617FE	1.85 - 1.93 x 1.54 - 1.69	47-49 x 39-43	20	\$89.01

Tee Compression x Compression x Compression	SIZE	PART NUMBER	PIPE DIAMETER RANGE		CTN QTY	LIST PRICE
			inches	millimeters		
				B		
NOTE: Assembled from Service Tee and Male Adapter						

90° Elbow Compression x Compression	SIZE	PART NUMBER	PIPE DIAMETER RANGE		CTN QTY	LIST PRICE
			inches	millimeters		
				BB		

Male Adapter Compression x MNPT	SIZE	PART NUMBER	PIPE DIAMETER RANGE		CTN QTY	LIST PRICE
			inches	millimeters		
				B x ¾		
	B x 1	75-6304B	0.83 - 1.06	21-27	80	\$23.84
	C x 1	75-6304C	1.06 - 1.34	27-34	50	\$47.74

Service Tee Compression x Compression x MNPT	SIZE	PART NUMBER	PIPE DIAMETER RANGE		CTN QTY	LIST PRICE
			inches	millimeters		
				B x ¾		

Installation Wrench	SIZE	PART NUMBER	PIPE DIAMETER RANGE		CTN QTY	LIST PRICE
			inches	millimeters		
				B - C		

(Call for other configurations)

**CAUTION:** Philmac<sup>®</sup> does not recommend or warrant the use of UTC<sup>®</sup> Compression Fittings "inside the building" or for "hot water" applications

# UTC SIZING CHART

The following chart provides a convenient means of identifying the appropriate UTC® fitting. UTC® fittings are available in sizes B, C, D, E, F, and G. Product may best be identified by the millimeter markings on the nuts.

- Recommendations are based on the variation in average diameter permitted by standard. Out of roundness effects are not considered. Call for pipes not listed.

- UTC® is pressure rated for 200psi at 73°F and 150psi at 100°F.

## UTC® SELECTION RECOMMENDATIONS

PIPE MATERIALS <sup>d</sup>	ASTM STANDARD	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"
Copper (Type K, L, & M)	B88	na	na	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	na
CTS PE or PEX	D2737 / F876	na	na	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	na
PVC (IPS-OD)	D2241 / D1785	<b>B</b>	na	<b>B<sup>a</sup> &amp; C</b>	<b>C<sup>a</sup> &amp; D</b>	<b>E</b>	<b>F</b>	<b>G</b>
ABS (IPS-OD)	D1527/ D2661/ F628	<b>B</b>	na	<b>B<sup>a</sup> &amp; C</b>	<b>C<sup>a</sup> &amp; D</b>	<b>E</b>	<b>F</b>	<b>G</b>
Galvanized Steel / Steel (IPS-OD)	A53	<b>B</b>	na	<b>B<sup>a</sup> &amp; C</b>	<b>C<sup>a</sup> &amp; D</b>	<b>E</b>	<b>F</b>	<b>G</b>
Stainless Steel <sup>c</sup>	A312 / A358 / A376	<b>B</b>	na	<b>B<sup>a</sup> &amp; C</b>	<b>C<sup>a</sup> &amp; D</b>	<b>E</b>	<b>F</b>	<b>G</b>
PE IPS-OD (SDR)	D3035 / D2447	<b>B</b>	na	<b>B<sup>a</sup> &amp; C</b>	<b>C<sup>a</sup> &amp; D</b>	<b>E</b>	<b>F</b>	<b>G</b>
PE SIDR 7 (IPS-ID)	D2239	na	na	<b>C</b>	<b>D</b>	na	na	na
PE SIDR 9 (IPS-ID)	D2239	na	na	<b>B</b>	<b>C</b>	na	na	na
PE SIDR 11.5 (IPS-ID)	D2239	na	na	<b>B</b>	<b>C</b>	<b>E</b>	<b>F<sup>a</sup></b>	na
PE SIDR 15 (IPS-ID)	D2239	na	na	<b>B</b>	<b>C</b>	<b>E</b>	na	<b>G</b>
Lead Strong		na	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	na	na
Extra Strong		<b>B</b>	<b>C</b>	<b>C</b>	<b>D</b>	na	na	na
Double Extra Strong <sup>b</sup>		<b>B</b>	<b>C</b>	<b>C<sup>b</sup> &amp; D<sup>b</sup></b>	<b>E</b>	<b>F</b>	na	na

na: not available - UTC® fitting for this size pipe is not available.

### NOTES:

- There may be occasions when the pipe is slightly too large for this UTC® size, in which case the coupling can be loaded on pipe disassembled.
- If the OD of the 3/4" "Double Extra Strong" lead pipe is larger than 1.34", use a Size D UTC® fitting or shave the pipe to fit a Size C UTC® fitting.
- Recommendations assume pipe is standard IPS diameter. Some pipe manufacturers may make pipe to other outside diameter dimensions.
- UTC is not recommended for PE-AL-PE and PEX-AL-PEX composite pipes.

**CAUTION:** Philmac does not recommend or warrant the use of UTC® Compression Fittings "inside the building" or for "hot water" applications.